



88 SHIELD

Protective water-oil repellent for marble, granite, natural stone, agglomerates

APPLICATIONS

88 SHIELD is an oil-water repellent for natural stones, limestone, marble, granite, terrazzo ecc.

88 SHIELD ensures a high degree of protection, is mark proof, and prevents general oil and dirt from sticking.

When it is used on surfaces previously treated with PRIMALAS/92, LITHOS or IDROSILAN it confers maximum protection as the products cited above protect against marks from rising damp, drop marks, pollution and acid rain.

HOW TO USE

Apply the product on a perfectly clean, dry and cold surface not exposed to sunlight and not during the hottest hours of the day, using a brush or better still with low pressure sprinklers with a 0.5 mm. nozzle or airless spray gun at a distance of around 20 cm from the surface. Any excess of product can be removed using a clean white cloth moistened with the product itself or a brush equipped with a soft disk. We suggest repeating the application of 88 SHIELD two to three hours after the first coat.

COVERAGE

Approx. 7-10 litres for every 100 sq.m. one coat, depending on the absorbency of the materials.

PRECAUTIONS

We suggest to test an inconspicuous area first to ascertain any change in colour of the materials to be treated.

PACKAGING

Bottle of 1 lt. Cartons of 12 pcs.

Tank of 5 lt. Cartons of 4 pcs.

Tank of 25 lt

WARNINGS

Refer to the MSDS available upon request.

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight at ventilated area. In these conditions, the product has a self-life of 24 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or

incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2023. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE