



ANTIQUE MARBRE HD 62 LUCIDO

Revitalizing protective solvent-based product for mineral substrates

WHAT IT IS USED FOR AND WHERE IT IS USED

ANTIQUE MARBRE HD62 LUCIDO is a solvent-based protective formulation based on selected resins, with exceptional clarity and resistant to the alkalinity of the substrate. Suitable for protecting mineral substrates in general such as exposed bricks, washed gravel, stone, etc.

HOW IT IS USED AND WHY IT IS USED

The product is applied directly on the surfaces to be treated, it can be applied by air spray, airless spray, roller or brush. In the case of spray application, the nozzle must be 1.9 - 2.2 mm and the pressure of 4 atm providing for the application of one / two coats. Application conditions: perfectly dry and clean surfaces with temperatures above + 5 ° C and between 25 - 30 ° C with relative humidity <85%. Do not apply the product in the presence of high atmospheric humidity, strong sun or strong wind.

QUANTITY OF USE

About 80-125 ml / m² per applied coat, variable according to the type of substrate for which the product is intended.

WARNINGS

Refer to the safety data sheet available on request.

PAKAGING

1 liter pack. Carton of 12/24 pieces

5 liters cans. Carton of 4/6 pieces
25 liters can

HANDLING AND STORAGE

The product must be stored in the original containers, hermetically sealed, at temperatures between 0 and 25 ° C, protected from direct sunlight and in a well-ventilated area. In these conditions, the product has a duration of 12 months from the date of the delivery note. If the material has been kept beyond the recommended shelf life, it is not necessarily unusable but a quality check must be carried out in advance on the characteristics relevant to the application.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not

imply liability on our part. As well as following good

working practices, before applying the product we recommend you read the

safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE