



# EXTRA YELLOW

*Extra-fine polishing powder for marble, onyx, cement-based agglomerates*

## CHARACTERISTICS:

**EXTRA YELLOW** is a polishing powder ideal for marbles, onyx, stones, and cement agglomerates. Thanks to innovative raw materials, its balanced composition, and extra-fine granulometry, it allows the polishing machine to glide more easily on the surface, ensuring faster processing. Available in the standard version or in the **EXTRA YELLOW WET** version, a moistened variant that does not release dust into the air, providing a wet effect on marble, Genoese floors, or cement tiles.

## APPLICATION:

**If polishing has been carried out with a traditional machine and abrasives:** after reaching at least grit 3/4, or preferably grit 4, place on the floor a small amount of powder (2 or 3 tablespoons), apply a pad or a soft sponge, and with the machine well aligned, slightly open the water valve and begin polishing a few square meters at a time. This will create on the surface a slurry with a consistency similar to yogurt or liquid cream, which will be used for polishing. The mixture should never be allowed to become too dry, as this would prevent the machine from gliding properly, nor too liquid, as this would not allow the correct chemical reaction. If too little water has been used and lapping marks have been created, simply go over the area again with the same method, but opening the water valve a bit more. Once the slurry has been

consumed, simply add more polishing powder without removing what is already on the surface. During polishing operations, it is advisable to check the gloss level obtained by removing the film from a small area with a cloth or squeegee. If necessary, repeat the process.

**If polishing has been carried out with a traditional machine using diamond tools or a single-disc machine:** polishing can be done after grit 400, or preferably grit 800. Then proceed as described above, using a pad/sponge or a white soft anti-scratch disc. At the end of the polishing treatment, it is recommended to remove all residue and wash with a neutral detergent such as **DETERGON R3** or with a water-repellent detergent such as **K-SOAP**, in order to obtain a clean, bright surface with temporary resistance to dirt, clean and protected joints, thus facilitating daily maintenance.

## WARNINGS

Before any application, carry out a preliminary test. The safety data sheet is available upon request.

## PACKAGING

Drum of 20 kg  
Drum of 5 kg

## HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight.

In these conditions, the product has a self life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

## RESPONSIBILITY LIMITS

We decline all responsibility for work or damage which may result from improper or incorrect use of the product. The information supplied on the characteristics and instructions on how to use derive from bibliography and from our laboratory experience. However as no other elements of proof can be forwarded when the products are used, said information must be intended as an outline and is not to be taken as a formal guarantee. No part of our technical sheets may be reproduced. The data refers to standards in force at the time of printing 2023. The Company reserves the right to make changes without notice.

**PRODUCT FOR  
PROFESSIONAL USE**