



SPEEDY WET

Non-dusty wet-look polishing powder for marbles, Genoese floors, and cement tiles

APPLICATIONS

SPEEDY WET is a non-dusty, high-acid-content polishing powder, ideal for the final stage of polishing to achieve mirror-like glossy surfaces. Suitable for use on all types of marble, marble-cement, agglomerates, and terrazzo. Thanks to the addition of special impregnating agents, it enhances the wet-look effect on treated surfaces.

HOW TO USE

Surface preparation is very important to ensure the best outcome of the work to be carried out: first of all, it is recommended to thoroughly clean the surface to be polished from any construction residues such as gravel, pins, etc. Then, apply 30 to 60 grams of product (2/3 tablespoons) per square meter, wet the powder until a creamy, milky consistency is obtained, place the traditional polishing machine equipped with felt or a weighted single-disc machine on the wet powder, and work the surface a few square meters at a time without ever letting it dry.

When in contact with water, the polishing powder will create a slurry with which the polishing is performed. This slurry should never be too dry, as it would prevent the machine from gliding properly, nor too liquid, as it would not allow the polish to achieve the correct chemical reaction. If not enough water has been used and lap marks appear on the polished surface, simply go over the area again using

the same method but opening the water valve more.

To check the progress of the polishing, it is recommended to remove the film from a small area using a rubber squeegee, in order to verify the level of gloss obtained and, if necessary, repeat the operation.

At the end of the polishing treatment, it is recommended to remove all the residue and then wash with a neutral detergent such as **DETERGON R3** or with a water-repellent detergent such as **K-SOAP**, ideal for obtaining a clean surface with excellent temporary resistance to dirt, clean and protected joints, and overall easier daily maintenance.

WARNINGS

Before any application, carry out a preliminary test. The safety data sheet is available upon request.

PACKAGING

Drum of 1-5-20 kg

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self life, it might still be suitable, but this has to be determined beforehand by performing quality

checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE