



Acrifloor

Let's shine

**Acrilic protective at 32% $\pm$ 2 of active
for mineral substrates and stamped floor**

CHARACTERISTICS

ACRIFLOOR is a solvent-based protective varnish based on selected acrylic resins, with exceptional clarity and resistant to the alkalinity of the substrate. Suitable for protecting, reviving and reinforcing plasters, concrete and mineral substrates in general (exposed bricks, washed grave exposed bricks, washed, stone, etc.). It resists the diffusion of carbon dioxide and therefore guarantees excellent protection against the carbonation of reinforced concrete.

HOW TO USE

PREPARATION OF THE PRODUCT: **ACRIFLOOR** is ready to use.

APPLICATION: it is applied directly on cement, stone, stucco, bricks and concrete. The product can be applied by air spray, airless spray, roller or brush. The nozzle must be 1.9-2.2 mm and the pressure at 4 atm. Number of coats: one or two. Application conditions: temperature above +5°C. relative humidity <85%. Do not apply the product in the presence of high atmospheric humidity, strong sun or strong wind.

INDICATIVE COVERAGE

80/125 ml per coat.

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it



25 Lt | 200 Lt



1000 Lt

STORAGE

The product must be stored in the original containers, hermetically closed, protect from direct sunlight and from frost. In these conditions the product has a shelf life of 12 months from the date of the delivery note, if the material will be kept in storage beyond the duration of recommended stability, will not necessary be considered unusable but must be performed a preventive check on the product.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2013. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE



is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it