



COVER

Finishing sealant for terracotta, Spanish terracotta, terracotta from Provence, Mediterranean terracotta, ceramic, non-glazed clinker and natural stone

APPLICATIONS

COVER is a impregnating finish for floors in terracotta, Spanish terracotta, terracotta from Provence, Mediterranean terracotta, ceramic, non-glazed clinker and natural stones, formulated with special carnauba and natural waxes in a synthetic resin carrier.

COVER was developed to complete the resin/wax treatment begun with the product **FEDERCOTT/C** neutral glossy or **FEDERCOTT/C** matt.

The resistance of **COVER** to acidic substances and ultraviolet rays renders it a product suitable for multiple applications.

It provides protection from deterioration and stains while respecting the breathability of the surface.

COVER represents the last phase of the treatment of terracotta which, while being the simplest, is of extreme importance the final result, to give the treated surface long-lasting protection against stains and streaks.

HOW TO USE

Twenty-four hours after applying **FEDERCOTT/C**, in order to obtain maximum protection, we recommend applying **COVER** sealant as the final phase of the treatment of terracotta. One coat is sufficient; spread by means of a roller, wax applicator, rag or brush being sure to spread the product well.

COVER produces a layer of protection and repels stains with

excellent resistance to water, abrasion and wear over time.

COVER gives the flooring a warm and glossy tone.

WARNINGS

The MSDS is available upon request.

PACKAGING

Bottle of 1kg. Box of 12/24 pcs
Drum of 5 kg. Box of 6 pcs

HANDLING AND STORAGE

The product **COVER** must be stored in the original containers, perfectly sealer, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part.

As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

**PRODUCT
PROFESSIONAL USE**

FOR