Federchemicals®

TECHNICAL DATA

CTF-40

Protective water-oil repellent for marble, granite, natural stone, terracotta, concrete, agglomerates

APPLICATIONS

CTF-40 is a solvent based oil-water repellent for the protection of medium and high absorbency building materials such Marble, Granite, Natural Stones, Terracotta, Concrete, Limestone, Agglomerates, Clinker, etc.

CTF-40 ensures a high degree of protection, is mark proof, and prevents general oil and dirt from sticking. It protects against smearing and graffiti by blocking the penetration of paints, making cleaning off easy.

When **CTF-40** is used on surfaces previously treated with **PRIMALAS/92**, **LITHOS** it confers maxi-mum protection as the products cited above protect against marks from rising damp, drop marks, pollution and acid rain. Floors and materials treated with **CTF-40** can be cleaned using normal neutral detergents.

HOW TO USE

Apply **CTF-40** to perfectly clean, dry, cold surfaces not exposed to sunlight and not during the hottest hours of the day, using a brush or better still with low pressure sprinklers with a 0.5 mm. nozzle or airless spray gun at a distance of around 20 cm from the surface. Any excess **CTF-40** can be removed using a clean white cloth moistened with the product itself or a brush equipped with a soft disk.

We suggest repeating the application of **CTF-40** two to three hours after the first coat. When used outdoors, wait until rain is not forecast for 12 hours.

PRECAUTIONS

Test an inconspicuous area first to ascertain any change in colour of the materials to be treated.

COVERAGE

Approx. 7-10 litres CTF-40 every 100 m² per coat, depending on the absorbency of the materials.

WARNINGS

Cover windows and surrounding vegetation with plastic sheets during application

The product contains ethyl acetates.

The MSDS is available upon request.

PACKAGING

Bottle of 1 lt. Box of 12/24 pcs

Drum of 5 lt. Box of 4 pcs.

Drum of 25 lt

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealer, at a temperature

between 0 and 25°C and shielded from direct sunlight. In these conditions, the product has a self-life of 24 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part.

As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE