

DERUGGY-STOP



Acid based product for removing rust stains and oxidation from light coloured granite

APPLICATIONS

DERUGGY-STOP is an acid based product used to remove rust stains from granite surfaces. It is especially effective to neutralise those elements in the granite that when exposed to atmospheric agents turn yellowish in colour thus impairing the material quality.

DERUGGY-STOP is effectively applied on such materials like Solar White, Camelia White, Kashmir, Panna Fragola, Bianco Kristal, Azularan, Rosa Beta and other types of light coloured granites. This product can be used by slab fabricators as well as on already laid surfaces.

HOW TO USE

For slab fabricators:

- Apply on polished slabs.
- Stir well before use.
- Apply **DERUGGY-STOP** evenly on the slabs (upwards on vertical surfaces), using a sprayer or a brush a plastic sheeting should be placed between the slabs (do not use wood).
- Leave for 1 to 12 hours depending on the intensity and amount of rust stains to remove.
- Rinse with plenty of clean, fresh water with a brush.

Attention: If applied undiluted on light coloured granite, **DERUGGY-STOP** might darken the surface. It is recommended to dilute as follows: 70 of product: 30 of water.

The efficacy of **DERUGGY-STOP** can be tested before application. **DERUGGY-STOP** can be applied on

a sample surface stained with rust: allow to absorb for about half an hour then heat the surface with a flame until perfectly dry. If the stain is removed, **DERUGGY-STOP** can be effectively used on the material treated. If the stain cannot be removed, contact our technical assistance. After the treatment with **DERUGGY-STOP**, it is recommended to apply **LITHOS** or **PRIMALAS/92** or **IDROSILAN** on the surface. These water repellents in fact, create a barrier between the material surface and atmospheric agents adding protection against oxidation.

PRECAUTIONS

Do not apply under direct sunlight.

COVERAGE

Consumption is variable and depends on the kind of surface. Approx. 1 lt for 10 sq.m.

WARNINGS

Refer to the MSDS available upon request.

PACKAGING

Bottle of 1 lt. Box of 12/24 pcs
Drum of 5 lt. Box of 6 pcs
Drum of 10 lt/25 lt

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 25°C and shielded from direct sunlight at ventilated area. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If

the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016.

The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE