



Distax DS

Let's shine

Release agent
for imprinted paving

CHARACTERISTICS

DISTAX DS is a dry, premixed release agent for moulds, ready to use and specially formulated for easy distribution on fresh concrete surfaces, to create imprinted and/or decorative paving. The formulation creates a fine, "imperceptible" layer that easily separates the mould from the fresh cement, and gives a "natural" shaded effect to imprinted paving. **DISTAX DS** is a non-stick powder formulated for use on surfaces treated with **DEKOCRETE QUARTZ**.

DISTAX DS is UV resistant as it is formulated with natural and synthetic carbonate iron oxides. It gives paving long-lasting deep shades and colour effects, and is compatible with colouring and shading treatments based on **ACID COLOR** acids, and with **ACRIFLOOR** finishing treatment.

HOW TO USE

Apply and spread in the ratio of 100 - 120 gr/m² in one or more passes.

CAUTION

Do not use on calcium chloride or calcium chloride-based products in the presence of coloured concretes.

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it

Distax DS

INDICATIVE COVERAGE

From 0.1 to 0.3 kg/m².

AVAILABLE COLOURS

Available in standard colours displayed in the colour chart. Personalised colours can be ordered on request for quantities over 1600 kg.

STORAGE

The product has a shelf life of 2 months if properly stored in its original packaging in a dry area. The product is supplied in plastic buckets to protect it from external agents and humidity, and the lid can be hermetically resealed to keep the product intact until it is reused.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2013. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE



12,6 kg



is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it