



Let's shine

Extra matt finish

CHARACTERISTICS

EXTRA MATT is a single-component impregnating emulsion with very high crosslinking, ideal for protecting natural stone and resin flooring as well as decorative vertical surfaces, acid etched flooring, decorative microcement flooring, concrete flooring, etc.

EXTRA MATT has a low VOC content and is suitable for indoor applications. The formulation gives treated surfaces a finish with excellent resistance to traffic and wear, whilst reducing the routine maintenance required. The very thin protective film not only guarantees excellent adhesion to the substrate, but also increases waterproofing and mechanical resistance to wear and scratches with an excellent anti-slip finish, and ensures excellent colour stability over time.

HOW TO USE

PREPARATION OF THE SUPPORT: the surfaces where **EXTRA MATT** is to be applied must be dry, clean, free of oil, grease or dirt in general. Substrates must be sound, compact and completely mature in the case of surfaces with a cement matrix.

PREPARATION OF THE PRODUCT: **EXTRA MATT** is ready to use.

APPLICATION: shake well before use then apply the first coat with a short-haired roller (short-haired mohair rollers specifically for polyurethane finishes) or with a wax spreader or airless turbine kit. Leave to dry for a minimum of 40 minutes (at +20°C), then apply a second coat perpendicular to the first. It must be applied at a temperature which is inferior to 10°C or superior to 30°C and with a residual humidity >70°C, these conditions can invalidate or slow down the dry of the product leading to unsightly results.

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - Fax +39 030 3385580

www.federchemicals.it info@federchemicals.it

Extra Matt



1 kg | 5 kg | 25 kg

INDICATIVE COVERAGE

1 lt for 10-20 square meters

STORAGE

The product must be stored in the original containers, hermetically closed, protect from direct sunlight and from frost. In these conditions the product has a shelf life of 12 months from the date of the delivery note, if the material will be kept in storage beyond the duration of recommended stability, will not necessarily be considered unusable but must be performed a preventive check on the product.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2013. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - Fax +39 030 3385580

www.federchemicals.it info@federchemicals.it