



FEDERCOTT/C

Sealing impregnating agent for flooring in tile made of terracotta, Spanish terracotta, terracotta from Provence, Mediterranean terracotta, ceramic, non-glazed clinker and natural stone

APPLICATIONS

FEDERCOTT/C is a complete sealant for flooring in terracotta, Spanish terracotta, terracotta from Provence, Mediterranean terracotta, ceramic, non-glazed clinker and natural stone, formulated with special carnauba and bees waxes in a synthetic resin carrier developed to resolve all those problems resulting from the need to not alter the visual effect, so that a perfect execution of the treatment can proceed. **FEDERCOTT/C**'s resistance to acidic substances and to ultraviolet rays render it a product suitable for multiple applications. It provides protection from stains and deterioration while respecting the breathability of the surface.

HOW TO USE

From the time, the surface is washed to the treatment with **FEDERCOTT/C** at least 2 summer days and 5-6 winter days must pass; in any case the flooring must at the most be humid (that is, there should not be any darkened tiles due to the water absorbed). It is essential, together with the sealing, to guarantee the terracotta protection against agents coming from the sub-base of the flooring using the product **SILOSILAN D.L.**, a water-based salt proof impregnator, taking care to apply the products at a temperature not lower than 10°C. Shake the product; pour the needed quantity in a basin (never return unused product to the container) and

spread it using a roller or brush taking care to spread it well. After 3-4 hours apply a second coat in the same manner. You will notice that **FEDERCOTT/C** is self-levelling and therefore does not leave streaks on the flooring. End the treatment phase by applying the resin-wax finish **COVER**. In the event it is necessary to remove the **FEDERCOTT/C**, use the solvent called **FEDERSOLV DW44** or **DEC** (water-based stripper) in the quantity and manner noted on the technical data sheets.

COVERAGE

For two coats: 1 kg for appr. 10-12 sq. depending on the absorption of the surface.

WARNINGS

The MSDS is available upon request.

PACKAGING

Bottle of 1 kg. Box of 12/24 pcs
Drum of 5 kg. Box 6 pcs

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by

performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE