



# FEDERCOTT/CA

*Base and finishing impregnating agent for terracotta tile*

## APPLICATIONS

**FEDERCOTT/CA** is a base and finishing impregnating agent composed of carnauba wax and resins emulsified in an aqueous dispersion for the aesthetic and functional treatment of terracotta for internal and semi-covered external use. **FEDERCOTT/CA** is a rich and homogeneous treatment with high penetrability leaving a natural gloss effect with excellent resistance to wear, high traffic, and colour retention.

## HOW TO USE

**FEDERCOTT/CA** is used just as it is. Before applying the product conduct a careful base cleaning with the detergent **DETERGON R3** or **BIOSAN**, after which, when the flooring is dry, proceed to the application. Pour the product in a basin and with the aid of a wax applicator, short pile roller or a brush, spread the product in a uniform manner applying two coats with an average of 4 hours between them (to be evaluated based on the temperature, the humidity and the surface). To increase the lustre of the treatment it is possible to polish the surface with a domestic polisher or with a brushing machine with a white pad. For normal cleaning, products such as **DETERGON R3** or **BIOSAN** which are pH neutral are recommended. For the maintenance of the lustre of the treatment use the product **LOOKING COTTO**, diluted in water according to the recommended dose.

## COVERAGE

For terracotta and ceramics with high absorbency: Approx. 11/15 kg per 100 sq.m. per coat.

For mechanical application or surfaces with medium absorbency: Approx. 10/12 kg per 100 sq.m. per coat.

## WARNINGS

Do not use alcohol or solvents for ordinary or special cleaning of the surface treated with **FEDERCOTT/CA**, avoid applying the product in the hottest hours of the day, avoid air currents during application, do not use at temperatures lower than 10° C or very high temperatures.

The MSDS is available upon request.

## PACKAGING

Bottle of 1 kg. Box of 12/24 pcs  
Drum of 5 kg. Box of 6 pcs

## HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

## LIMITS

## OF

## RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

## PRODUCT

## FOR

## PROFESSIONAL USE