

GLEND STONE

Self-polishing varnish for granite and marble edges



APPLICATIONS

Thanks to its special formula, the self-polishing, transparent and colourless **GLEND STONE** can be applied to marble, granite, natural stone and to all absorbent rough materials. It protects and polishes at the same time backs, steps, fireplaces, corners and small surfaces which could hardly be polished mechanically. More coats can be applied whenever necessary.

The product is not sticky and it penetrates deep into the porosities of marble and granite without filming, granting a long service life even when applied outdoors.

HOW TO USE

Apply **GLEND STONE** onto clean and dry surfaces using a brush or tampon, and rub in to avoid heaps on surface.

To bring out the gloss, when dry and after using the abrasive paper No. 4, we recommend using a portable angular lapping machine within 3000/8000 rpm, fitted with a merino felt.

N.B.: To obtain a satin or semigloss finish, rub evenly using fine steel wool after drying.

WARNINGS

The MSDS is available upon request.

PACKAGING

Can of 750 ml. Box of 12/24 pcs

HANDLING

STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS

RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the

AND

results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE