



HM 2

Multi use water based water repellent

APPLICATIONS

HM2 has a special formulation which makes the surface water repellent while leaving its aesthetic characteristics and substrate transpirability unchanged. It can be applied on all masonry materials such as: gypsum, cement, lime, stone, bricks, roof tiles and agglomerates. It gives the surface an invisible protection and adds in durability and resistance against wear due to weather agents. It is a water repellent and prevents water from penetrating inside walls thus avoiding frost during winter and risk of damage and cracking. It prevents fluorescence and mould build-ups. It does not create a continuous film, but penetrates covering the inner surface of each pore.

HOW TO USE

HM2 can be applied with a normal large brush or sprayed (low pressure). Before applying the product, the surface must be cleaned of any efflorescence and moulds using **SANNY KAL** or **CLEAN SPECIAL**, depending on the masonry work to treat, then rinse. It is advised to apply the product after 1 or 2 days, when perfectly dry. **HM2** is applied in one coat uniformly.

PRECAUTIONS

Apply **HM2** only on cleaned cold and dry surfaces. It is advised to protect the treated surfaces from rain for 24 hours until the water repellent film is formed completely. If wrap-shrink films are used to pack materials treated with **HM2** on pallets, make sure proper adequate aeration holes are provided to allow full water repellent action and

complete drying. It is always recommended to test the material to treat for proper results. Do not apply the product in areas with strong chlorine or aluminous cement substrates.

COVERAGE

1 litre for approx. 5-20 square meter depending on the type of surface.

PACKAGING

Bottle 1 lt. Box of 12/24 pcs

Drum 5 lt. Box 6 pcs

Drum 10 lt/25 lt

WARNINGS

Refer to the MSDS available upon request.

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 25°C and shielded from direct sunlight in ventilated area. In these conditions, the product has a self-life of 24 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work, damage or storage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in

the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part.

As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden.

The data refer to the standards in force at the time of printing, 2016.

The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE