



# IDROBASE 303

*Ecological in-depth water-based oil and water-repellent product with anti-stain*

## APPLICATIONS

**IDROBASE** is a fast water-based water and oil-repellent sealer with anti-mustiness properties, it is an one-component product for medium and high porosity surface; conservative product for depth and surface; non-filmogenic treatment, it penetrates deeply into building materials, protecting them from the absorption of water, leaving the materials completely breathable. The product reduces greatly the absorption of liquid, oily or fatty substances, and does not alter normally the natural appearance of terracotta and natural stones, making the cleaning simpler.

## HOW TO USE

Apply the product to a clean, perfectly dry surface, or slightly wet using a polish spreader, a short-haired roller, a flat brush or a low-pressure spray gun and wait for 24 hours before possible applying resin / wax treatment.

For external works, it is advisable to wait two to three days after the washing when the surface becomes completely dry and then apply the product in max.2-3 coats, with 3-4 hours between each coat. The oil-water-repellent protective property is reached after 24/48 hours and depending on the amount of applied product hands.

After drying, remove any excess product with a soft and dry cloth, or with a single brush giving to the treated surface an original gloss.

## COVERAGE

Natural stone: Approx. 8/12 litres every 100 sq.m. per coat,

according to the porosity of the surface.

Very porous terracotta: Approx. 12/15 lt every 100 sq.m. per coat.

Mechanical terracotta: Approx. 10/12 lt every 100 sq.m. per coat.

## PRECAUTIONS

Do not apply the product in the sun or on hot surfaces.

## WARNINGS

Refer to the MSDS available upon request.

## PACKAGING

Can of 1 lt. Box of 12/24 pcs

Drum of 5 lt. Box of 6 pcs

Drum of 10 lt

Drum of 25 lt

## HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealer, at a temperature between 5 and 30°C and shielded from direct sunlight at ventilated area. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

## LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field.

However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016.

The company reserves the right to make any changes without notice.

## PRODUCT FOR PROFESSIONAL USE