

IMPRIM RTF

Corrector for granites, marbles, natural stones



APPLICATIONS

IMPRIM RTF Corrector is a product which, with the addition of special pigments, is used to darken black marbles and granites such as: Africa Black, Zimbabwe Black, green marbles and granites type: Alp Green, Guatemala Green, red marbles and granites, and dark granites in general, giving these a wet look, livening up the colours for many years and restoring even the most faded colours. Its application livens up colour tone in all those materials with little or inadequate natural colour and where a quality surface corrector is required. The product reduces surface faults such as the slight marks that develop during the smoothing and/or polishing of marble, granite and natural stone surfaces.

IMPRIM RTF Corrector can be used on all stone surfaces to bring to light even the most faded colours and recover and renew worn surfaces (such as floors, stairs, window-sills, balustrades and tables, etc.) because the special features of this product enhance colour and at the same time strengthen the surface structure. The product is stable under UV rays and is therefore also recommended for outdoor use.

HOW TO USE

The product corrects any surface faults in marbles, granites and natural stone of the "polished type" in a natural and long-lasting way. Shake the container well before using, because the pigments tend to deposit on the bottom. The surfaces to be treated must first of all be cleaned and perfectly dried. Apply the product with a short-haired roller and with

a clean soft-cotton cloth, spreading it evenly. Avoid excess product stagnating and drying on the surface. Wait 24 hours to permit absorption and then remove all excess product from the surface using a home polishing machine or brush equipped with felts or fine steel wool disc. If necessary, repeat the treatment operation by applying a second coat in the same way as the first. The product does not form a film and several coats can be applied. Before applying the second coat, it is not strictly necessary to wait 21 hours before removing excess product. This can in fact be removed after 4/5 hours from application using the brush equipped with felts or fine steel wool disc. Do not use water until 96 hours have passed from treatment with "**IMPRIM RTF**".

PRECAUTIONS

Product application is irreversible and once applied it cannot therefore be removed. For better professional use, always perform a preliminary test in a small hidden area to check product compatibility with the desired effect and determine consumption.

WARNINGS

The MSDS is available upon request.

PACKAGING

Bottle of 1 lt. Box of 12/24 pcs
Drum of 5 lt. Box of 6 pcs.
Drum of 10 lt/25 lt/200lt

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealer, at a temperature between 0 and 30°C and shielded from direct sunlight. In these

conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

**PRODUCT FOR
PROFESSIONAL USE**

Rev.01 25.08.2017

