



IPS 1000

Rusteater

APPLICATIONS

IPS 1000 is a specifically formulated product for removing rust stains from all stone materials: granite, marble, limestone, terracotta and ceramics. It does not contain acids and can therefore be used also on polished surfaces without affecting their shine.

It acts quickly and easily removes rust.

HOW TO USE

Dampen the surface slightly with clean water and then apply a uniform layer of IPS 1000 to the stained area (about 5 mm thickness), using a spatula (not made of metal).

Spread the product evenly over the stained area then allow to react. The product colour changes from transparent yellowish to dark purplish as the reaction takes place.

The reaction duration may vary even greatly depending on the type of material and finish. It is therefore advisable to always test a small area of the surface, for compatibility and application times.

It is to be noted that the reaction duration varies greatly and polished surfaces generally require longer application times (around 5 minutes).

On light and crystalline materials if a persistent halo occurs after the removal of the rust, localized application of hydrogen peroxide is recommended.

Once the reaction is completed, it is advisable to remove any residue and rinse with plenty of clean water. Rinse again if necessary.

PRECAUTIONS

Do not leave the product on the surface for more than 10-15 minutes, in order to prevent it from penetrating deep into the substrate.

WARNINGS

The MSDS is available upon request.

PACKAGING

Bottle of 1 lt. Box 15 pieces.

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might

still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS

RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read

the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE