

IPS/3000

Stain remover for oily and greasy substances



APPLICATIONS

IPS/3000 is a solvent-based gel stain remover quietly foaming, expressly studied for the specific removal of stains of organic and alimentary nature: it removes oily and greasy stains.

The gel formulation allows a prolonged action of the active substances and the presence of wetting agents help in destroying the stains the product **IPS/3000** is used for. It is active until the total drying. If necessary, repeat the stain-removal action.

It is suitable for any kind of organic stain not excessively penetrated in depth, and for any kind of greasy stain: dregs, sludges, wax, smog environmental stains, lamp-black, etc.

IPS/3000 can be used on any kind of stony surface both porous and not porous. Do not use on rubber, linoleum and synthetics, painted wood, etc.

HOW TO USE

Apply a layer of product of around 5 mm height over the stain to remove, using a spatula; cover with a transparent film or plastic film to let the product works into a humid environment. Three hours after application, remove the film and let it dry. When the paste is completely dry, after around 8-10 hours, depending on room temperature, it will have a whitish color.

Proceed with the removal or residue with a brush. After removing the marks and when the surface is clean and perfectly dry, we recommend treatment with a hydro-oil repellent, mark defender product such as: REP-OIL NEW, KERASTONE or IDROBASE 303 to protect the surfaces from all oil-soluble substances.

WARNINGS

The MSDS is available upon request.

PACKAGING

Pot of 250 ml.

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealer, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect

use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2024. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE