



KEOS/928

Stainproof, non-slip impregnator inhibiting absorption of water and greasy substances. For protection of surfaces made of "polished" natural stone

APPLICATIONS

KEOS/928 is a water-oil repellent impregnating, containing organic, aromatic solvents with slow evaporation, with a high penetration capacity also on surfaces with a poor absorbency, such as Slate. **KEOS/928** has excellent anti-stain properties for both horizontal or vertical surfaces made of "polished" natural stone (i.e.: marble, granite, marble agglomerates (grits, Venetian Mosaic, Terrazzo); product enables an easier removal of normal or exceptional dirt. **KEOS/928** applied outdoors has high resistance to atmospheric agents and corrosion caused by acid rain.

HOW TO USE

Dilution: To be used undiluted.

Application: Apply evenly using a flat brush, polish spreader or short-haired roller; it is also possible to use an airless spray-gun with 0,5÷1 bar nozzle. After 24 hours, the excess product should be removed from surface using a single-brush machine equipped with white or beige wheel, or a floor polisher fitted with felts, or a dry cloth.

Should some excess product remain on surface, it will then be necessary to apply another thin coat of **KEOS/928**, to be immediately dried and removed by a rag.

N.B.: It is recommended to test the product on a small portion of

surface to check for any possible alteration in colour.

For the protection of rough natural stone surfaces, apply **KEOS / 928** uniformly in a brush or coated roller and after 24 hours finish the water-repellent treatment with two coats of **WAXSTONE** or with a **CERAMARMO** (1 coat) and finish with two coats of **WAXSTONE**.

COVERAGE

Natural stones, marbles, smoothed granite: approx. 4-5 litres per 100 sq.

Absorbent unpolished natural stones: approx. 5-10 litres per 100 sq.

WARNINGS

Refer to the MSDS available upon request.

PACKAGING

Can of 1 lt. Box of 12/24 pcs

Drum of 5 lt. Box of 6 pcs

Drum of 10 lt/25 lt

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight at ventilated area. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality

checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE