

LOOKING COTTO



Re-polishable neutral maintenance wax for terracotta

APPLICATIONS

The product **LOOKING COTTO** is an emulsified neutral re-polishable liquid wax for maintenance in the treatment of terracotta (both antique and modern). It is easy to apply and allows the attainment of a semi-gloss and natural shine on surfaces previously treated with resin-wax treatments. Flooring treated with **LOOKING COTTO** is protected from wear and stains and cleaning and maintenance operations are facilitated. In addition, the product prevents signs resulting from high traffic. It is a rich and homogeneous treatment with high attaching power to resin-wax treatments with excellent resistance to wear, high traffic, and colour retention.

HOW TO USE

Before applying the product conduct a careful base cleaning with the detergent **DETERGON R3** or **BIOSAN**, after which, when the flooring is dry, proceed to the application. Pour 2-3 cups of the product in a basin or bucket and dilute with approximately 10 litres of water. Apply it with a uniformly damp soft rag. Let the product dry for approximately 20 minutes, after which polish it with felt, a wool pad or domestic polishing machine.

If the flooring was previously treated with other types of wax, before applying **LOOKING COTTO** clean and strip the former wax using a water based stripper called **DEC**. For normal maintenance cleaning, products such as **DETERGON R3** or

BIOSAN which are pH neutral are recommended.

COVERAGE

Approx. 1 kg for every 100 sq.m.

PRECAUTIONS

Do not use alcohol or solvents for ordinary or special cleaning of the surface treated with **LOOKING COTTO**.

Avoid applying the product in the hottest hours of the day, avoid air currents during application.

Do not use at temperatures lower than 10° C or very high temperatures.

WARNINGS

Refer to the MSDS available upon request.

PACKAGING

Bottle of 1 kg. Box 12/24 pcs

Drum of 5 kg. Box 6 pcs

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight at ventilated area. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might

result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.