

LUX

Special paste wax based on Brazilian carnauba and very precious natural beeswaxes for marble, granite and natural stone



APPLICATIONS

LUX is a paste wax formulated with very precious natural waxes dispersed in organic solvent to cure and protect marble, granite, natural stones, agglomerates (grits, Venetian mosaics, terrazzo). LUX is a very fine wax obtained by mixing the best Brazilian carnauba and beeswaxes; it guarantees marble and granite floors long-lasting protection meanwhile they maintain their natural shine. It creates a dirt-repellent barrier and increases the beauty of the surfaces. Pure beeswax, one of the precious ingredients of product, besides oil of turpentine from pine buds make LUX a perfect wax polish which gives new light to floors.

HOW TO USE

Dilution: to be used undiluted.

Application: Two coats of product should be applied at an interval of 4 to 5 hours between each one. Apply thin an even layer and spread the wax using a normal synthetic sponge, a rag or a flat brush. It is also possible to apply the wax using a single-brush machine equipped with a small heating stove and medium-soft brushes. Allow to dry for a few hours then rub with a dry woollen cloth or felt pad or single-brush polisher fitted with white or beige disks. The floor will soon acquire a beautiful shine. Do not use too much wax at a time: LUX wax has among its main components the purest beeswax

that needs to be spread in small quantities to attain the best result. LUX leaves no smears, is dust and humidity repellent, thanks to its waterproofing properties.

COVERAGE

Approx. 6 lt per 100 sq.m. per coat.

PRECAUTIONS

The paste wax tends to thicken in winter; we recommend placing the tin in hot water or next to a radiator to restore it to its fluid state. Never heat the product on naked flames. The paste waxes with solvent base are inflammable. The product should be mixed up before use.

WARNINGS

Refer to the MSDS available upon request.

PACKAGING

Can of 1 lt. Box of 12/24 pcs
Drum of 5 lt. Box of 4 pcs

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0°C and 30°C and shielded from direct sunlight at ventilated area. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be

determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2020.

The company reserves the right to make any changes without notice.

**PRODUCT
PROFESSIONAL**

**FOR
USE**