



Oil Blocker

Let's shine

High-performance single-component
protective agent

CHARACTERISTICS

OIL BLOCKER è is a water-based impregnating agent, ideal for protecting concrete surfaces and absorbent building surfaces such as: bricks, natural stones, reconstructed stones and similar materials.

OIL BLOCKER is a water-based product with very low odor, formulated with new high-performance silane-siloxane polymers, ideal for obtaining excellent repellency to oily substances and water, furthermore the product is non-flammable, very simple to use, does not form unsightly films and lets the surfaces breathe where applied.

OIL BLOCKER increases the life of the substrate and keeps the functional aesthetic characteristics of the support unchanged for a long time, also reduces the damage caused by freezing / thawing and salt efflorescence.

HOW TO USE

PREPARATION OF THE PRODUCT: **OIL BLOCKER** is ready to use, it is not necessary to dilute it.

APPLICATION: on a clean and perfectly dry surface, at most slightly damp, apply the product with airless spray system at low pressure; the consumption varies according to the porosity of the surface, it can be considered an average use of 1 liter every 8-10 m². It is possible to spread one or two coats according to the surface porosity, the second coat can be given "wet on wet" when the first coat is not yet polymerized. Do not leave excesses of product on the surface, the oil-repellent protective capacity is

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it

Oil Blocker



5 Lt | 25 Lt

obtained after 24/48 hours from application and depending on the quantity of product applied. The drying time depends on the atmospheric conditions (temperature, humidity, wind, etc.), do not apply at temperatures below 8 ° C, on hot surfaces or under direct sunlight. Maximum protection will develop within 4-6 days of application.

CAUTION

Make sure you are in possession of the latest version of technical data sheet and safety data sheet; please read the information contained therein before using the product.

INDICATIVE COVERAGE

Variable from 8 to 10 m² with 1 litre, depending on the porosity of the surface.

STORAGE

The product must be stored in original containers, hermetically closed, at a temperature between 10°C and 30°C, protected from direct sunlight and in ventilated areas. In these conditions the product has a shelf life of 12 months from the date of the delivery note, if the material will be kept in storage beyond the duration of the recommended stability, will not necessarily be considered unusable but must be performed a preventive check on the product.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2013. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it