

PRO H2O

Color enhancing dirt protector



APPLICATIONS

PRO H2O is an anti-dirt protective agent in aqueous solution specific for lapped stoneware floors. It preserves the surface from stains of various nature (clomping and similar) and increase greatly the resistance to dirt; it makes easier subsequent ordinary cleaning and increases the shine of the original treated surfaces.

HOW TO USE

The product can be used both on production lines and after laying.

Automatic application:

After possible washing, dry the surface of the stoneware with the air conveyors and apply the product by roller, spreading it evenly over the entire surface and remove the excess with tampico or similar disks.

Manual application:

On surface perfectly dry and clean, apply a coat of product evenly with a brush, fleece or other suitable applicator, taking care to work a few meters at a time and spread the product on both the tile and the joints. After a few minutes on a dry surface, use a mono-brush with a white disc. The surface can be walked on after 12/24 hours from treatment. The second coat is applied a few hours after the surface is dried. The product crosses completely in 48 hours at a temperature of 20C.

COVERAGE

Automatic application: Approx. 20/35 gr per sq.m. depending on the surface to treat, method of application and environment temperature.

Manual application: Approx. 1 lt per 30/45 sq.m.

PRECAUTIONS

Do not apply the product at temperatures below 10 ° C or on hot surfaces or in the sun. Protect the

surface from water within the first 24 hours of treatment.

It is always advisable to carry out a preliminary test online to verify the exact coverage and compatibility.

WARNINGS

Refet to the MSDS available upon request.

Before any application, carry out a preliminary test.

PACKAGING

Bottle 1 lt. Box of 12 pcs.

Tank 5 lt. Box 4 pcs.

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealer, at a temperature between 5 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product or from inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety

recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE