



REP-OIL NEW

Protective oil-water repellent for granite, marble, natural stone, conglomerates, grits, cement, terra cotta for indoors and outdoors spaces

APPLICATIONS

REP-OIL NEW is an oil-water repellent based on synergized fluoride copolymers with high chemical inertia mixed with organic solvents. This product supplies significant and specific protection and combats marking with its water repellent action against rising damp and oil repellent action against spills.

The product penetrates the surface offering the highest degree of protection against the infiltration of external substances such as oil, fats, coffee, fruit juice, drinks: they also prevent the formation of lime-scale and marks caused by algae, lichen and even those from dampness and acid rain. This is a specific product also for work tops and the floors of kitchens and bathrooms. **REP-OIL NEW** is recommended for absorbent building materials such: natural stone, marble, granite, porphyry, conglomerates, cement, terracotta, both indoors and outdoors. **REP-OIL NEW** does not significantly alter the tonality of the treated materials and protects well against graffiti. Floors and surfaces treated with it can be cleaned with normal neutral water-based detergents.

HOW TO USE

Apply **REP-OIL NEW** to perfectly clean, dry, cold surfaces not exposed to direct sunlight and not during the hottest hours of the day, using a brush or better still with low pressure sprinklers or airless spray gun at a distance of around 20 cm from the surface. Any excess **REP-OIL NEW**

can be removed using a clean white cloth moistened with the product itself or a brush equipped with a soft disk. We suggest repeating the application of **REP-OIL NEW** two to three hours after the first coat. When used outdoors, wait until rain is not forecast for 12 hours.

PRECAUTIONS

Do not apply the product at high temperatures on hot surfaces or in the sun.

Before any application, carry out a preliminary test.

COVERAGE

Approx. 7/10 litres every 100 m² per coat, depending on the absorbency of the materials.

WARNINGS

Refer to the MSDS is available upon request.

PACKAGING

Can of 1 lt. Box of 12/24 pcs
Drum of 5 lt. Box of 6 pcs
Drum of 10 lt/25 lt

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight at ventilated area. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by

performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice

PRODUCT FOR PROFESSIONAL USE