

RUSTSTOP/G

Special acid product for removing rust and oxidation from granite



APPLICATIONS

RUSTSTOP/G is a specific product specially formulated to remove any type of rust present in granite rich in iron minerals. Recommended for use both on rough, polished and dressed granite and it is suitable for the application on materials such as Kashmire white, Panna fragola, Cristal white, Camelia white, Solar white etc.

The product is also available in the LSB version, specifically formulated for Luserna stone, serizzo, and beola.

HOW TO USE

Apply the product evenly on the surfaces of the slabs to be treated, even placing them upright, using a sprinkler or a brush covered with a cloth and making sure to start from the bottom and working upwards paying attention not to allow the product to drip. Use plastic spacers to keep the slabs separated from each other and allow the product to work for 2/3 hours or more, up to 10/12 hours, according to the quantity and the persistence of the stains that have to be removed. Then rinse thoroughly with clean water.

PRECAUTIONS

To avoid possible slight darkening of lighter coloured materials we recommend diluting **RUSTSTOP/G** with water (seven parts products and three parts water).

Use the same method to treat the floors.

Following treatment with **RUSTSTOP/G** we recommend applying a protective water repellent such **LITHOS** and a water-oil repellent such as **KEOS/928** or **KERASTONE**, to be applied on a perfectly clean and dry surface in order to avoid that the atmospheric agents give origin to oxidative processes on the materials.

Important: carry out a trial test on a small part of the surface to check the efficacy of the product on the material to be treated.

WARNINGS

The MSDS is available upon request.

PACKAGING

Bottles of 1 kg. box of 12 pcs.

Drum of kg 5. Box of 4 pcs.

Drum of 10 kg

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between +0 and +25°C and shielded from direct sunlight in ventilated area. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS

OF

RESPONSIBILITY

We decline all responsibility for work, damage or storage which might result from improper or incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part.

As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2020. The company reserves the right to make any changes without notice.

**PRODUCT
PROFESSIONAL**

**FOR
USE**