



SANNY KAL

Acid scale remover to take off dirt after flooring operations and for the initial washing of horizontal or vertical acid-resistant surfaces

APPLICATIONS

SANNY KAL buffered and scented is a powerful concentrated acid detergent containing corrosion inhibitors, which do not develop harmful fumes. It has in-depth action on porous, non-calcareous materials, removes laying residues and has excellent properties against saline efflorescence. It is the ideal product to clean surfaces made of terracotta, clinker, red stoneware, ceramics, normal porcelain stoneware and acid-resistant natural stones.

HOW TO USE

Dilution: **SANNY KAL** should be diluted at 1:5, 2:10 ratios, according to the scales to be removed.

Application: Distribute the solution on the surface and let it act for a few minutes according to the type of dirt or calcareous scales to be removed. Go over with a mop or a single brush machine equipped with a black or brown abrasive disk. Rinse thoroughly and collect liquid residues using rags or a liquid-vacuum machine.

Should any surface part not be perfectly clean, repeat the operation until cleaning will be completed or use a more concentrated solution. Rinse carefully with clean water.

PRECAUTIONS

SANNY KAL must not be applied on polished marble or materials non-resistant to acids (such as black or grey slate) and certain types of ceramics or polished stoneware.

Before cleaning this kind of tiles, a sample test should be made to check their resistance to the product. **SANNY KAL** (acid) must not be applied on metal.

COVERAGE

Terracotta floorings: Approx. 10-15 litres per 100 sq.m. diluted 2:10 (according to the type of material and the degree of dirt or calcareous scale).

Natural stones: Approx. 4-5 litres per 100 sq.m. diluted 1:10 (according to the type of material and the degree of dirt and calcareous scales).

WARNINGS

SANNY KAL is an irritating product for eyes and skin, we recommend the use of acid-resistant gloves, protective goggles and rubber footwear. In case of contact, wash with plenty of water.

The MSDS is available upon request.

PACKAGING

Bottle of 1 lt. Box 12/24 pcs
Drum of 5 lt. Box 6 pcs
Drum of 10 lt/25 lt

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for

longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS

OF

RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

PRODUCT

PROFESSIONAL

FOR

USE

