

SILOSILAN D.L.

Water-repellent anti-saltpetre, anti-mold based on water for brick, brick-to-sight bricks, cement and absorbent natural stones



APPLICATIONS

SILOSILAN D.L. is a high-quality water-based water repellent product. It is a stable alkaline and acid priming agent. It contains wetting agents and can be applied on any fire clay based mineral substratum, such as: baked clay, terracotta, exposed brickwork, roofing tiles, cement, natural stones and absorbent marble surfaces.

HOW TO USE

SILOSILAN D.L. ready for use should not be diluted, but applied pure.

SILOSILAN D.L. active base is being diluted at ratio 1 lt. of product in 10 lt. of water according to the absorption capacity of the material to be treated.

Preliminary treatment for tiles joints: It is recommended to use the **SILOSILAN D.L.** product as a pre-treatment for dirt from sealing on all highly absorbent surfaces; apply a uniform spray or brush on the entire surface, after 48-72 hours it will be possible to make the grout avoiding "burns" and halving machining times.

Preliminary treatment: Before start washing on hand-made cooked surfaces, cooked Spanish, Mediterranean cooked, Provençal cooked or any very absorbent terracotta or terracotta, it is advisable to sweep the surfaces well, soak them with water (ie dampen them) and then apply a large amount of **SILOSILAN DL**. After 24-48 hours a good water repellence of depth, antisalnitrite,

anti-mold, anti-efflorescence will be obtained and the surface is ready to be washed with **SANNY KAL**.

On exposed bricks apply **SILOSILAN** in 2 coats and at an interval of 2/3 hours one from another, **SILOSILAN D.L.** has a high resistance to acid rain and atmospheric agents and a hydrophobic capacity of about 8-10 years and does not change the chromatic appearance of the treated surfaces.

The application of **SILOSILAN D.L.** is by spray or with hair roller.

COVERAGE

Hand-made terracotta: approx.. 7/8 m² per litre.

Mechanical terracotta: approx. 10/12 m² per litre.

WARNINGS

Refer to the MSDS available upon request.

PACKAGING

Bottle of 1 lt. Box of 12/24 pcs

Drum of 5 lt. Box of 6 pcs

Drum of 10 lt/25 lt

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 5 and 30°C and shielded from direct sunlight in ventilated area. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by

performing quality checks on its application-related properties.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

**PRODUCT
PROFESSIONAL**

**FOR
USE**