



SOFT CLEAN

Delicate acid detergent for surface depth cleaning and for removing patina and residues

APPLICATIONS

SOFT CLEAN is a perfumed acid cleaner and limescale remover especially effective for removing any laying residues and building grime from stoneware, ceramics, acid-resistant natural stones and quartz resin agglomerate. Its rapid and delicate action solubilizes limescale and lifts it from grout thus making its complete removal easier during washing. It is also suitable for cleaning floors blackened by resistant stains, foot traffic, hard water and smog.

HOW TO USE

Dilute the product with cold and clean water to the concentration from 1:3 to 1:5 depending on the type of dirt or the tenacity of residues to remove.

It can be used non-diluted for removing of surface patina very strong and tied to surfaces.

Spread the solution on the surface and work it with scrubbing or with a single-disc floor scrubbing brush. Let the product from 5 to 15 minutes, during this time it is recommended to continue massaging the surface; once this work is finished, to remove the residues and rinse plenty with water.

COVERAGE

1 Lt for approx. 15/20 sq.m. depending on the type and quantity of dirt as well as dilution.

PRECAUTIONS

Do not use on non-acid-resistant materials such as: polished marble, limestone or metallized and lapped stoneware. Always test a small inconspicuous area for compatibility. Do not mix with bleach or any cleaner that contains bleach.

PACKAGING

Bottle 1 lt. Box of 12/24 pcs

Drum 5 lt. Box 6 pcs

WARNINGS

Refer to the MSDS available upon request.

HANDLING AND STORAGE

The product must be stored in the original containers, perfectly sealer, at a temperature between 5 and 30°C and shielded from direct sunlight in ventilated area. In these conditions, the product has a self-life of 24 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

LIMITS

RESPONSIBILITY

We decline all responsibility for work, damage or storage which might result from improper or

incorrect use of the product or inadequate storage. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part.

As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden.

The data refer to the standards in force at the time of printing, 2016.

The company reserves the right to make any changes without notice.

PRODUCT

PROFESSIONAL USE

FOR