

Super Shine

Let's shine

Finishing protective polishing treatment
for concrete surfaces

CHARACTERISTICS

SUPER SHINE is a polishing finishing product with high content of solids into aqueous dispersion for mirror finishing of concrete surfaces subjected to high pedestrian stress like offices, shops, commercial centers.

SUPER SHINE is a breathable finishing with high and pleasant visual effect, that hardens quickly and easy to apply, suitable to be used in structures where maximum protection and minimum downtimes are required, ensuring a long-lasting protection and giving uniformity to the superficial treatment after mechanical polishing.

HOW TO USE

PREPARATION OF THE SUPPORT: after consolidation of the surface and after honing with resinoid abrasives until grain 800, we suggest remove any eventual superficial powder trough suction or light wash with washing machine.

PREPARATION OF THE PRODUCT: use the product pure.

APPLICATION: on perfectly dry and clean surface, apply a uniform and fine coat, with a microfiber pad, of the product **SUPER SHINE**; let the surface dry for at least 60 minutes. If necessary, repeat the application, avoiding excesses of product, since they can create antiesthetic results or whitening.

After complete drying (60 minutes at least), we suggest pass on the surface with a high-speed polisher (2000/2500 rpm) using a pad with natural bristles in order to increase the shine of the treated surface trough greater thermal reaction. Complete drying takes normally 1 or 2 hours. We suggest avoid washing surface for at least 7 days after treatment, to avoid eventual antiesthetic reactions, since the treatment will reach the complete cross-linking in this period.

The treatment is considered for internal use, it must not be applied at a

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it

Super Shine



25 lt

temperature lower than 5°, in the event that temperatures are too hot, it could be useful to moisten the surface in advance with water to avoid that the product dries too fast. In the event that the product is applied in a too cold or humid environment, these conditions slow down the dry of the product; whenever an hour has passed since the application and the floor should be too wet, it is recommended to clean the surface with an automatic floor buffer to remove the excessive product.

CAUTION

Avoid contact with surfaces to which the product is not intended. Protect from frost. Make sure of having the last update of the technical datasheet and the safety one; please, read the information before any use of the product.

INDICATIVE COVERAGE

Variable from 15 to 40 m² with 1 litre, depending on the porosity of the concrete surface.

STORAGE

The product must be stored in the original containers, tightly sealed, at temperature between 10°C and 30°C, protect from direct sunlight and in ventilated areas. In these conditions the product has a duration of 12 months from the date of the delivery note. If the material will be kept in storage beyond the recommended stability period, it will not necessarily be considered unusable but a quality control must be performed on the characteristics relevant to the application.

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package.

For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing.

The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2013. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE

Let's shine  is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it