



Xilo 1

Let's shine

Solvent-based acrylic resin thinner

CHARACTERISTICS

XILO 1 is a solvent specially formulated for diluting solvent-based acrylic resins from the **Federchemicals** range and for cleaning the equipment used for their application. It can also be used as a flow improver to enhance the workability of the resins.

HOW TO USE

The product is ready to use.

AS A DILUENT: use **XILO 1** following the instructions provided in the product datasheet it is intended for.

AS A CLEANER: remove fresh resin by immersing the cleaning equipment in a container containing **XILO 1** or by rubbing the surfaces to be cleaned with a cloth soaked in the product. Dispose of the product residues according to the current waste disposal regulations.

TECHNICAL DATA

Appearance	Transparent liquid
Odor	Characteristic of solvent
Relative density	0,87 Kg/Lt
Flash point	$23 \leq T \leq 60$ °C
VOC (Directive 2010/75/CE)	100,00 % - 869,19 g/liter
VOC (volatile organic compound)	87,58 % - 761,21 g/liter

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it



25 lt

STORAGE

The product has a shelf life of 24 months from the delivery note date, provided it is stored indoors, in sealed packaging, protected from heat sources and freezing, at a temperature between +5°C and 30°C. If the material has been stored beyond the recommended storage stability duration, it may not necessarily be unusable, but a qualitative check on the application-related characteristics should be carried out beforehand..

LIMITS OF RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2013. The company reserves the right to make any changes without notice.

PRODUCT FOR PROFESSIONAL USE

Let's shine is a line:

FEDERCHEMICALS™ s.r.l.

Via G. Borsi, 2 - 25128 Brescia - Italy

Tel. +39 030 3385578 - info@federchemicals.it

www.federchemicals.it