

ZIMBABLACK

Surface corrector for granites, marbles, natural stones



APPLICATIONS

ZIMBABLACK is a long-lasting sealant formulated to saturate surfaces and to cover the stains present in black Zimbabwe. **ZIMBABLACK** is a product which with the addition of special pigments is used to darken black marble and granite such as: Black Africa, Black Zimbabwe, Black Marquinia, etc and green granites such as: Alpine Green, Guatemala Green, etc giving them a wet look and refreshing the colours for several years and restoring the brilliance to those dulled colours, possible only through the use of a quality surface corrector. The product reduces the surface defects such as slight scratches produced during the various smoothing and/or polishing phases of the marble, granite or natural stone surfaces. The product is stable under UV rays so it can be applied on external surfaces. The treated surfaces become darker, have a more uniform appearance and quality is improved.

HOW TO USE

Manual: allow ZIMBABLACK to drip onto the dry horizontal slabs, then spread evenly using paper or a clean, dry cloth.

Automatic: apply the product using a neutral polishing machine or added with pigments as required.

Slabs smoothes at 1200: make sure the slab is perfectly dry. Using a roller or brush, apply

evenly on the slab preferably placed flat down. Allow to dry for at least 48 hours. Finish polishing using polishing heads (2 or 3 heads).

PRECAUTIONS

Do not apply ZIMBABLACK on wet slabs or on those which have previously been treated with other materials.

COVERAGE

Approx. 1 litre for 25 m².

WARNINGS

The MSDS is available upon request.

PACKAGING

Bottle of 1 lt. Box of 12/24 pcs
Drum of 5 lt. Box of 6 pcs
Tank of 10 lt/25 lt/200 lt

HANDLING

STORAGE

The product must be stored in the original containers, perfectly sealed, at a temperature between 0 and 30°C and shielded from direct sunlight. In these conditions, the product has a self-life of 12 months of the date quoted in the delivery note. If the material has been stored for longer than its recommended self-life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties.

AND

LIMITS OF

RESPONSIBILITY

We decline all responsibility for work and damage which might result from improper or incorrect use of the product. The indications supplied with our product specifications and instructions for use are the results of accurate laboratory tests and experience in the field. However, as it is not possible to forward other evidence, when the products are used, these indications shall not be binding and do not imply liability on our part. As well as following good working practices, before applying the product we recommend you read the safety recommendations and the directions on the package. For the best professional results, it is advised to test a small area first, for compatibility with the surface to treat and the desired effect. This preliminary testing is also useful to determine the consumption according to the characteristics of the material the product will be used for and to the type of processing. The reproduction, even partial of this product sheet is forbidden. The data refer to the standards in force at the time of printing, 2016. The company reserves the right to make any changes without notice.

**PRODUCT
PROFESSIONAL**

**FOR
USE**